
			CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland			Name and address of manufacturer
DOP13REV3 MEDITE PREMIER FR MDF EUROCLASS C			DoP reference.
EN 13986:2004+A1:2015			Reference to harmonised standard
Warrington Certification Limited 1121			Notified body number
04			Year in which the CE mark was first affixed
E1			Formaldehyde classification
MDF			Product technical class
Internal use as non-structural components in dry conditions			Intended use
<b>Thickness Range mm</b>	4 to 6	>6 to <9	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.65	0.65	Declared performance
<b>Swelling in thickness %</b>	30	17	
<b>Reaction to fire</b>	C-s2,d0	C-s2,d0	
<b>Release of formaldehyde</b>	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	
<b>Biological Durability</b>	Use Class 1		

				CE symbol
Medite Europe Limited, Redmondstown, Clonmel, Co. Tipperary, Ireland				Name and address of manufacturer
DOP12REV3 MEDITE PREMIER FR L-MDF EUROCLASS C				DoP reference.
EN 13986:2004+A1:2015				Reference to harmonised standard
Warrington Certification Limited 1121				Notified body number
04				Year in which the CE mark was first affixed
E1				Formaldehyde classification
L-MDF				Product technical class
Internal use as non-structural components in dry conditions				Intended use
<b>Thickness Range mm</b>	9 to 12	>12 to 19	>19 to 25	Thickness range
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.45	0.45	0.45	Declared performance
<b>Swelling in thickness %</b>	16	14	12	
<b>Reaction to fire</b>	C-s2,d0	C-s2,d0	C-s2,d0	
<b>Release of formaldehyde</b>	E1	E1	E1	
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	
<b>Biological</b>	Use Class 1			