



In order to claim any defect covered by these warranties the following conditions apply:

- The quality control system within the factory should be able to control and prove that the requirements outlined in the specification are fulfilled.
- In the event of a claim Drywood Coatings BV should be informed immediately.
- If any defects occur, repair should take place within 3 months to minimize subsequent damage.
- In case of a claim Drywood Coatings BV is entitled to investigate the claim by having access to the joinery being claimed and all relevant data from the production process.
- Costs for repair of damaged covered by this warranty will only be reimbursed if Drywood Coatings BV has given a written approval before the actual expenditure.
- For X10 warranty regular inspections of the product process and the quality control systems by Drywood Coatings BV are required.

In other respects, our general terms and conditions are applicable as stated in the general sales conditions of V.V.V.F. (Vereniging van Verf- en Drukinktfabrikanten) in the Netherlands.

Our warranties apply to full weathering in a mild in-land European climate on south-west orientation of timber at at least 10 cm set back installation of the facade. Exposure in coastal, mountainous or industrial areas or at high building levels or installation more outside the façade decreases the written warranties. Longer warranties can be applied to low exposure at north-east orientation or under roofs or timber positioned more than 15 cm inside the façade.



Drywood Coatings: coating systems for MEDITE TRICOYA EXTREME

Durable and stable wooden MDF boards of MEDITE TRICOYA EXTREME in exterior applications ask for a durable coating of Drywood Coatings. Because of the extreme low shrinkage and swelling of this substrate and its high resistance against degradation this board material can be coated with our extremely durable and very low-maintenance coating systems with maintenance interval up to 15 years.



Drywood Coatings has been developing extremely durable coating systems since 1960 and has more than fifty years of experience with the performance of water borne coatings. The combination of MEDITE TRICOYA EXTREME and Drywood Coatings exterior coating systems has been tested for adhesion and durability under severe alternating water immersion and drying tests. This resulted in the following coating systems to be recommend for use on Medite Tricoya for façade panels, cladding, sidings, parts of window-frames and doors.

DRYWOOD FACTORY FINISHED SYSTEMS:

- Spraying two layers of Optifinish G40.
- Spraying two layers of Optiprimer G and finish the front side and edges at the construction site with for instance Poseidon UV GL.
- Spraying three layers of Optifinish TR SG or GL (tinted).

Damage repair with DRYWOOD Poseidon UV (TR) SG or GL (also for maintenance).

DRYWOOD SEMI-FILMBUILDING SYSTEM:

- Spraying three layers of Woodstain VV (tinted) and two layers on backside (system for cladding and sidings only).

Damage repair with DRYWOOD Woodstain VV (also for maintenance).



DRYWOOD Coatings also has a comprehensive product range of brushable primers and finishes for perfect finishing, re-pairing or maintenance. Our finished systems have an average layer thickness of 150 µm with a minimum of 140 µm. For Tricoya it is necessary to apply a coating system on both sides. For a long life application, it is important to apply the boards on a well ventilated construction and the surface should not be in permanent contact with water. Apply two layers of DRYWOOD Endgrain Sealer TR on the end grains with intermediate sanding.

To keep the coating system in optimal condition, **DRYWOOD Coatings** advises yearly washing of the surface, inspection on (and repair of) failures and application of one layer of **DRYWOOD OptiProtect** maintenance lotion. A superior maintenance friendly system till 15 years — less dirt pick up, more colour- and gloss retention — is possible for instance with **DRYWOOD Poseidon UV** or **Woodpaint Nova**. Ask for the conditions as well as the other specifications.

We invite you to contact us for more information, also to inform you about our complete product range for the entire wood working industry and about all our brush paints for construction and renovation.

Drywood Coatings B.V.

**H. ter Kuilestraat 181 • NL-7547 SK ENSCHEDE • Postbus 3954 • NL-7500 DZ ENSCHEDE
T: +31 (0)53 433 4422 • F: +31 (0)53 430 6832 • E: info@drywood.nl • W: www.drywood.nl
KvK 06043784**